

PLB101

High auto loader

● Capacity

Power		3phases 200V 60Hz	3phases 220V 60Hz	3phases 200V 50Hz
Blower capacity	Output	0.93 kW	0.93 kW	0.76 kW
Carry performance *1		185 kg/h		

*1 It is the value which used of bulk specific gravity 0.65 g/cm³ virgin material for level 9 m and perpendicular 3 m and Ø 38 mm hose piping, and was measured in our company.

And this value is the case where a supply place is a vacuum cyclone PS1. (at 60 Hz)

● Standard specifications

Dust collecting method	Body	Dust filter box	
	Filter	Dust filter	
Safety device	Error contents	Safety device	Error notification mode
	Earth leakage	Earth leakage circuit breaker	Power OFF
	Overload	(with overload protector)	
	Phase reversal	Reverse phase protection relay	Display lamp+Operation stop
	Blower motor overload	Overload relay	Display lamp+Operation stop
	Clean filter	Notification timer	Display lamp
Colour *2	A45-90A (Gloss)		

*2 The colour (paint colour) may be changed according to the customer's request.

● Accessories

Power cord	3.5 m
Hose	Ø38 mm x 20 m (L) (without earth wire)
Hose band	4 pieces for Ø 38 mm hose

● Utilities


Power		3phases 200V 60Hz	3phases 220V 60Hz	3phases 200V 50Hz
Electric capacity		0.93 kW	0.93 kW	0.76 kW
Rated current		4.6 A	4.3 A	3.6 A
Earth leakage circuit breaker capacity		15 A		
Air	Pressure	Not required		
Size		W 536 x D 529 x H 1147 (mm)		
Weight *3		50 kg		

*3 Weight of a standard model

PLB101

High auto loader

● Outline view



□ Specification may be changed without prior notice.

NAKAMURA