

PLB401

High auto loader

● Capacity

Power		3 phases 200 V 60 Hz	3 phases 220 V 60 Hz	3 phases 200 V 50 Hz
Blower capacity	Output	2.55 kW	2.55 kW	2.20 kW
Carry performance *1		730 kg/h		

*1 It is the value which used of bulk specific gravity 0.65 g/cm³ virgin material for level 9 m and perpendicular 3 m and Ø 50 mm hose piping, and was measured in our company.

And this value is the case where a supply place is a vacuum cyclone PS1. (at 60 Hz)

● Standard specifications

Dust collecting method	Body	Dust filter box	
	Filter	Dust filter	
Safety device	Error contents	Safety device	Error notification mode
	Earth leakage	Earth leakage circuit breaker (with overload protector)	Power OFF
	Overload		
	Phase reversal	Reverse phase protection relay	Display lamp+Operation stop
	Blower motor overload	Overload relay	Display lamp+Operation stop
Clean Filter	Notification timer	Display lamp	
Colour *2	A45-90A (Gloss)		

*2 The colour (paint colour) may be changed according to the customer's request.

● Accessories

Power cord	3.5 m
Hose	Ø 50 mm x 20 m (L) (without earth wire)
Hose band	4 pieces for Ø 50 mm hose

● Utilities


Power		3 phases 200 V 60 Hz	3 phases 220 V 60 Hz	3 phases 200 V 50 Hz
Electric capacity		2.55 kW	2.55 kW	2.20 kW
Rated current		12.5 A	11.7 A	9 A
Earth leakage circuit breaker capacity		20 A		
Air	Pressure	Not required		
Size		W 536 × D 529 × H 1147 (mm)		
Weight *3		70 kg		

*3 Weight of a standard model

PLB401

High auto loader

● Outline view



□ Specification may be changed without prior notice.

NAKAMURA